



BELAMI

MANUFACTURERS & EXPORTERS
OF LABORATORY & FINE CHEMICALS
ESTD. 1957

SPECIFICATION SHEET

AMMONIUM CERRIC NITRATE AR

[REAGENT GRADE]

$(\text{NH}_4)_2[\text{Ce}(\text{NO}_3)_6]$

MW 548. 23

AMMONIUM HEXANITRATOCERATE

SPECIFICATIONS: REAGENT GRADE

ASSAY [DRY BASIS] : Min 99. 0%
ACID INSOLUBLE MATTER: MAX 0.005%
LOSS ON DRYING : MAX 3 %
CHLORIDE (Cl): Max 0.001%
SULPHATE (SO₄): Max 0.025 %
COPPER (Cu) : MAX 0. 0005%
IRON (Fe) : MAX 0. 002%
LEAD (Pb) : MAX 0. 001%
POTASSIUM (K): MAX 0. 005%
SODIUM (Na) : MAX 0. 005% %

PACKING : 25/50 Kg HDPE DRUM
UN HAZARD CODE: 5.1 / 1477
CAS # : 16774-21-3
HS CODE : 2846 10 00

APPLICATIONS:
REAGENT

BELAMI FINE CHEMICALS PVT.LTD.

29, GOPAL BHUVAN, 2ND FLOOR, 199 PRINCESS STREET, MUMBAI- 400 002.
Tel.: +91-22-2205 1092/ 93· Fax: 91-22-22019611 • E-mail: belamifinechem@gmail.com URL: www.belamifinechem.com